

**WHAT IS CLAIMED IS:**

1. In a traffic control system for coordinated operation of a plurality of traffic control lights and pedestrian advisory signs having potentially conflicting states; a malfunction management unit having input terminals for receiving control signals used to operate the traffic control lights and pedestrian advisory signs,  
5 monitoring means for detecting a conflict between a flashing DON'T WALK input signal and other traffic control signals; and an output for controlling the operation of an output relay used to transfer the operation of the traffic control lights to a flashing mode of operation when a conflict is detected.

10

2. The invention of claim 1 wherein said malfunction management unit includes a manually settable switch for enabling and disabling said monitoring means.

15

3. The invention of claim 1 wherein said malfunction management unit includes a display for indicating whether said monitoring means is enabled.

20

4. The invention of claim 3 wherein said control signals are assigned to channels; and wherein said display includes a plurality of display units assigned to different channels to indicate those channels for which said monitoring means is enabled.

5. A method of monitoring for conflicts between flashing DON'T WALK pedestrian advisory sign control signals and other control signals used to operate traffic control lights, said method comprising the steps of:

- (d) detecting a flashing DON'T WALK pedestrian advisory sign control signal;
- 25 (e) detecting the states of the other control signals;
- (f) generating a fault signal when a conflict occurs between a flashing DON'T WALK signal and the other control signals.

30

6. The invention of claim 5 wherein said pedestrian advisory sign control signals and said other control signals are grouped in a plurality of channels; and wherein said method further includes the step of providing a display of those channels on which said steps (a) and (b) are enabled.

7. The invention of claim 5 further including the step of manually enabling the performance of steps (a) and (b).